EasyQCL-1000 :

High-Power Terahertz Quantum Cascade Laser System


LONGWAVE PHOTONICS

The EasyQCL-1000 system is our latest generation of turnkey terahertz Quantum Cascade Laser source, offering average power levels of up to 20 mW* thanks to the more powerful Pulse Tube cryocooler. The system is configurable with a wide range of QCLs emitting at discrete frequencies between 1.9 and 5 THz in CW/pulsed and single/multimode. Multiple QCLs can be mounted in the same cooler (Multi-QCL option), and is available on request.

- ☐ The EasyQCL-1000 system Includes:
 - QCL laser diode module
 - Closed cycle single stage Pulse Tube Cryocoole
 - QCL drive electronics capable of pulsed or continuous wave operation (<0.4 µs up to DC)
 - All necessary accessories for turnkey operation
- ☐ A variety of user interchangeable QCL modules are available:
 - 10's of Milli-watt average power levels
 - Continuous wave operation available at select frequencies
 - Choice of center frequencies ranging from 1.9 to 5 THz
 - Multimode operation
 - Single mode DFB output at select frequencies
- ☐ The EasyQCL-1000 system is designed for ease of use:
 - Cryogen free laser diode cooling is by closed cycle refrigeration
 - · No optical alignment
 - · Cooler is maintenance free
 - Main system is tabletop compact and operates on 240 V single phase power source
- Applications:
 - High power Illumination source for focal plane arrays
 - Noise and responsivity Characterization of detectors
 - Local oscillator to pump Schottky-diode mixers for heterodyne detection



EasyQCL-1000 Main body (with compressor detached)



THz QCL Submount

* At select frequencies, see **QCL Power and Spectra Data Sheet**.

EasyQCL-1000 Technical Data

Included Components:

- QCL device(s) characterized for wavelength, output power, beam divergence and current versus voltage
- Vacuum chamber with electrical feedthroughs and vacuum gauge
- · Liquid/Air cooled, Pulse-Tube cryocooler
- LWP-PS2 pulsed laser driver or DC power supply (for CW operation)
- · Compact rotary vane vacuum pump
- Laptop PC with software for control of the driver and cryocooler

QCL Characteristics:

- Multimode and single mode laser diodes available.
- Beam divergence from 5 to 35 degrees FWHM
- · Select devices operable in continuous wave

LWP-PS2 Laser Driver Specifications:

QCL Driver Electronics (FPO typical values):

Current: Up to 2 A
Voltage: Up to 100 V
Pulsed width: 0.2 µs up to DC
Frequency: 100 Hz to 100 KHz

Triggering: TTL Internal/External Gate

BNC connector

Interface: USB

Compatibility: Windows 7/8.1

Software Options: Laser bias current/voltage,

pulse width, duty cycle and trigger source (internal

external)

AC voltage range: 100 - 125 / 200 - 240 V

Rated frequency: 50 - 60 Hz

Rated Current: 120 V/5 A – 240 V/ 2.5 A

Interface/Control: USB

Pulse-Tube Cryocooler Specifications:

- · Room Temperature, no cryogens.
- Cooldown time < 30 min to ~50 K
- Maintenance: Cold head requires periodic vacuum purge to ~10⁻² mbar with provided compact vacuum pump (e.g. Edwards E2M0.7 or similar). No turbo pumping required.

AC voltage range: 200VAC / 208-230VAC

Rated frequency: 50 / 60 Hz
Rated Power Consumption: 3.5 kW / 4.2 kW
Operating modes: Open Loop

(Close Loop Temperature Control Package available on request)

Warranty

- · One year parts and labor
- First compressor maintenance: 15,000 Hours

Dimensions

Cooler:


approx 7 x 7 x 21 in (17 x 17 x 52 cm)

Compressor:

20 x 22 x 22 in (50 x 56 x 56 cm)

Weight:


Cooler: ~10 kg Compressor: ~80 kg




Approximate Dimensions in inches [mm]


Applications

Illumination source for THz imaging






High Quality Beam for pumping heterodyne mixer



Beam focused using f/1 dia/25 mm High Resistivity Silicon Lens onto NEC IRV-TO831 Focal Plane Array

Single Mode Radiations for High Resolution Spectroscopy



LongWave Photonics LLC 958 San Leandro Ave Ste 300 Mountain View, CA 94043

Tel: (617)-399-6405 Fax: (617)-399-6406

info@longwavephotonics.com

Copyright © LongWave Photonics LLC, 2014